



DESCRIPTION:


- Adjustable LED tracklight with excellent optical performance and maximum eye comfort. Designed with an anti-glare ring to provide ultra-lighting performance.
- Ideal for office, commercial, leisure, hospitality and retail applications.
- CRI 90, UGR < 19, efficacy of up to 103.5lm/w and an output of up to 2900lm.
- Specific rotation control to 0-355°. Narrow, medium and wide beam angles available for different lighting applications. Complete family of products of different sizes.



TECHNICAL:

Mains Voltage (V): 220-240
Power (W): 28
Ingress Protection (IP): 20
Optional (IP): -
MacAdam Ellipse: 3 Step MacAdams
CRI: >90
UGR: <19

Efficiency (lm/W): 103.5
Operating Temp (oC): 25°
Operating Hours: 50,000
Optic Diffuser: Lens
Finish: White or Black
Warranty: 5 Years
Installation: Tracklight



SPECIFICATION:



UGR
< 19



White Bezel Black Bezel



Please contact us for other specific product options, variants and finishes: hello@chiaralighting.com

HOW TO ORDER: Fill out the Code Builder on the next page



Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification.

Chiara Lighting Ltd | Unit 18, Calderdale Business Park, Club Lane, Halifax, HX2 8DB United Kingdom
T: +44 (0)330 0571 888 | E: hello@chiaralighting.com | W: www.chiaralighting.com





LED Tracklight

Code Builder

| MODEL | CRI | CCT | WATTAGE | BEAM | BEZEL FINISH | BAFFLE FINISH | CONTROL | ACCESSORIES |
|-------------------------|------------------|---|-------------------|---|--|--------------------|--|-------------------------|
| Pure M (PureM) | >90 (9) | 2700K (27) 3000K (30) 4000K (40) | 28W (28) | 18° (18) 30° (30) 45° (45) | White (W) Black (B) | Black (B) | Switched (S) Phase Dim (PD) DALI (DA) Casambi (C) | Honeycomb (HC) |

Example code:

PureM — **9** — **27** — **28** — **18** — **W** — **B** — **S** — **HC**

PureM.9.27.28.18.W.B.S.HC

LUMEN OUTPUT

2700K = 2500lm

3000K = 2700lm

4000K = 2900lm