



**DESCRIPTION:**

- Adjustable LED tracklight with excellent optical performance and maximum eye comfort. Designed with an anti-glare ring to provide ultra-lighting performance.
- Ideal for office, commercial, leisure, hospitality and retail applications.
- CRI 90, UGR < 19, efficacy of up to 86.7lm/w and an output of up to 1700lm.
- CRI80 option.
- Specific rotation control to 0-355°. Narrow, medium and wide beam angles available for different lighting applications. Complete family of products of different sizes.




Family of Products



**TECHNICAL:**

Mains Voltage (V): 220  
 Power (W): Up to 21  
 Ingress Protection (IP): 20  
 Optional (IP): -  
 MacAdam Ellipse: 3  
 CRI: >90  
 UGR: <19



Efficiency (lm/W): 86.7  
 Operating Temp (oC): 25°  
 Operating Hours: 50,000  
 Optic Diffuser: Lens  
 Warranty: 5 Years  
 Installation: Track



**SPECIFICATION:**



**UGR**  
**< 19**



Please contact us for other specific product options, variants and finishes: [hello@chiaralighting.com](mailto:hello@chiaralighting.com)

**HOW TO ORDER:** Fill out the Code Builder on the next page



Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification.

Chiara Lighting Ltd | Unit 18, Calderdale Business Park, Club Lane, Halifax, HX2 8DB United Kingdom  
 T: +44 (0)330 0571 888 | E: [hello@chiaralighting.com](mailto:hello@chiaralighting.com) | W: [www.chiaralighting.com](http://www.chiaralighting.com)





MODEL	CRI	CCT	WATTAGE	BEAM	BEZEL FINISH	BAFFLE FINISH	CONTROL	ACCESSORIES
Pure S ( <b>PureS</b> )	>90 ( <b>9</b> )	2700K ( <b>27</b> )	15W ( <b>15</b> )	15° ( <b>15</b> )	White ( <b>W</b> )	Black ( <b>B</b> )	Switched ( <b>S</b> )	Honeycomb ( <b>HC</b> )
	>80 ( <b>8</b> )	3000K ( <b>30</b> )	21W ( <b>21</b> )	25° ( <b>25</b> )	Black ( <b>B</b> )		Phase Dim ( <b>PD</b> )	
		4000K ( <b>40</b> )		30° ( <b>30</b> )			DALI ( <b>DA</b> )	

Example code:

**PureS** — **9** — **27** — **15** — **15** — **W** — **B** — **S** — **HC**

**PureS.9.27.15.15.W.B.S.HC**

LUMEN OUTPUT - CRI90	
15W	21W
2700K = 1100lm	2700K = 1500lm
3000K = 1200lm	3000K = 1600lm
4000K = 1300lm	4000K = 1700lm